

IMAGE



FINISHING

Upholstery Available In Fabric or Leather
 Available C.O.M. / C.O.L.

Required Fabric For Upholstery: 1,50 Lm / 4.92 ff
 With Back In Wood: 1,00 Lm / 3.28 ff
 Required Leather For Upholstery: 1,90 Sq m / 20.45 ff²
 With Back In Wood: 1,30 Sq m / 13.99 ff²

Gross Weight: 12 Kg / 26.46 lb
 Volume: 0,42 Cbm / 14.83 ff³
 Box Dimensions: w 730 x d 680 x h 830 / 28.74" x 26.77" x 32.68"
 1 per box

SIZE



STANDARD FEATURES

INNER FRAME

Double radius stratified curved beech plywood, warm shaped, 14 mm thick. Various wood essences are available. Foam moulded polyurethane, density 40 kg/m³.

PADDING

Seat & back foam made of flexible polyurethane, crushproof, density D40/RC thickness 30 mm, rear back D40/RC thickness 0,5 mm. CFC-free.

BEARING FRAME

Union of two symmetrical bended shapes in beech thickness 14 mm foldaway combined through special glues and through 3 steel blades fixed with special screws Wurth®.

REAR BACK FINISHES

Made in veneer with a thickness of 1 mm, High Light-fastness. Natural Finishing.

Available with visible wood essences Wengé & Oak.

All components used are made in full compliance with EC regulations, E1 class materials, FSC Certified.

BASE

Swivel base, four-spoke, polished aluminium, 631 mm. diameter (Lead is present in the aluminum to a lesser extent <0.20%), The aluminum used complies with 2005/95/CE, 2002/69/CE and 2003/108/CE). Recyclability 100%.

MECHANISM

Fixed plate without lever. AutoReturn mechanism. With this new system, the chair rotates to the original position. Made of round solid steel, worked in the lathe with inner spring covered by an insert made of Teflon (PTFE) to guarantee the perfect rotation, reduces friction and wear.

FEET

Chrome ABS feet, suitable for any type of flooring, lower part made of polyamide 6, ivory.

OTHERS

-Stitching's Are Made With Continuous Filament Polyester Thread With A Water Repellent Finish Made By Coats® Type Weaverbird™ This Type Of Lubricated Polyester (Tkt 010) Thread Make The Stitching Stronger, Resistant To The Abrasion, And Gives The Product More Tailoring Appearance. Allowing To Read The Forms And Design Of The Product

-All screws and assembly systems used in the production of Sitia's product are UNI EN ISO 9001-2000 and UNI ISO/TS 16949 process certified.

Sitia srl Copyright 2016 - all rights reserved. The described data could be modified without prior communication